

 INTERNATIONAL TOWING TANK CONFERENCE	ITTC – Recommended Procedures and Guidelines	7.6 – 01 - 01 Appendix 2 Page 1 of 2	
	Sample Work Instructions Measuring Equipment Sample of Calibration Certificate	Effective Date 1999	Revision 00

ANNEX 2.: SAMPLE OF CALIBRATION CERTIFICATE.

QM 4.10.6.2	CALIBRATION CERTIFICATE for PROPELLER DYNAMOMETER	NO. <input style="width: 80%;" type="text"/>	
		LIN <input style="width: 80%;" type="text"/>	
Calibration Instructions	<input style="width: 100%;" type="text"/>	Calibrated by :	<input style="width: 100%;" type="text"/>
Date of calibration	<input style="width: 100%;" type="text"/>	Checked by :	<input style="width: 100%;" type="text"/>
Measurement combination			
DYNAMOMETER LIN <input style="width: 80%;" type="text"/>	Manufacturer <input style="width: 100%;" type="text"/> Serial No <input style="width: 100%;" type="text"/> Work instruction <input style="width: 100%;" type="text"/>	Model <input style="width: 100%;" type="text"/> Date of purchased <input style="width: 100%;" type="text"/> Last calibration <input style="width: 100%;" type="text"/>	
Cable			
AMPLIFIER L <input style="width: 80%;" type="text"/>	Manufacturer <input style="width: 100%;" type="text"/> Serial No <input style="width: 100%;" type="text"/> Work instruction <input style="width: 100%;" type="text"/> Excitation <input style="width: 100%;" type="text"/>	Model <input style="width: 100%;" type="text"/> Date of purchased <input style="width: 100%;" type="text"/> Type of transducer <input style="width: 100%;" type="text"/> Frequency of excit. <input style="width: 100%;" type="text"/>	
Cable			
A/C TRANSDUCER L <input style="width: 80%;" type="text"/>	Manufacturer <input style="width: 100%;" type="text"/> Serial No <input style="width: 100%;" type="text"/> Work instruction <input style="width: 100%;" type="text"/>	Model <input style="width: 100%;" type="text"/> Date of purchased <input style="width: 100%;" type="text"/> Certificate No <input style="width: 100%;" type="text"/>	
MEASUREMENT STANDARDS			
MEASUREMENT STANDARDS	Mass <input style="width: 100%;" type="text"/> Length arm of force <input style="width: 100%;" type="text"/> Voltmeter <input style="width: 100%;" type="text"/>	Certificate No <input style="width: 100%;" type="text"/> Certificate No <input style="width: 100%;" type="text"/> Certificate No <input style="width: 100%;" type="text"/>	

Prepared	Approved
22 nd ITTC QS Group	22 nd ITTC 1999
Date	Date



**ITTC – Recommended
Procedures and Guidelines s**

**7.6 – 01 - 01
Appendix 2
Page 2 of 2**

**Sample Work Instructions
Measuring Equipment
Sample of Calibration Certificate**

Effective Date
1999

Revision
00

QM 4.10.6.2				CALIBRATION RESULTS			
Environmental condition							
Place of test :							
Temperature :	initial		final				
Dampness :	initial		final				
Computation results of calibrations test							
Executed program	procedure	certificate NO.					
	Thrust	Torque					
Drift :							
Non Linearity errors :							
Hysteresis :							
Precision errors :							
Total uncertainty :							
Calibration factor :							
Calibration requests :							
Specified limits of	Thrust	Torque					
errors :							
Maximum capacity :							
Minimum capacity :							
Note : tests and computations results are included in report							

Prepared by : Approved by : Date :